

「Spanpixel」シリーズ

SSF = LCD Panel + LED駆動回路

SSH = SSF + ADボード

SSD = SSH + 筐体

2024/6/5

型番	0635-T	1393-A	1505-E	1515-E	1624-B	1725-B	1875-B
サイズ (インチ)	6.2" (7" cut1/2)	13.9" (17" cut1/2)	15" (19" cut1/4)	15.9" (19" cut1/2)	16.3" (18.5" cut1/3)	17.2" (18.5" cut2/3)	18.7" (21.5" cut1/10)
提供可能 モデル	SSF/SSH	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD
有効表示 領域(mm)	153.6(H)x37.5(V)	337.92(H)x105.14(V)	376.3(H)x71.2(V)	376.3(H)x150.5(V)	409.8(H)x71.4(V)	409.8(H)x153(V)	476.06(H) x36.2(V)
輝度 (cd/m ²)	1000 cd/m ²	600 cd/m ²	1000 cd/m ²	1000 cd/m ²	350 cd/m ²	1000 cd/m ²	1000 cd/m ²
解像度	1024x250	1280x398	1280x242	1280x512	1366x238	1366x510	1920x146
視野角	150° (H), 145° (V)	170° (H), 160° (V)	160° (H), 170° (V)	170° (H), 160° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)
消費電力 (W)	3.2W	21W	12W	15W	8.8W	17.4W	9.7W
外形寸法 (WxHxD mm)	165.75x55x3.85	360.9x132.5x48.6	410x108.2x39.3	398.4x176.2x52.7	436.3x100.2x43	432.9x181.1x40	499.6x54.3x31.8

1

※ 消費電力・外形寸法は、SSDの仕様値です。該当品がない場合は、それに準ずる製品の仕様値です。
 ※ 本仕様は予告なく変更されることがあります。
 ※ 最新データは、<http://plazmonic.jp/files/Spanpixel.pdf>をご参照ください。








「Spanpixel」シリーズ

SSF = LCD Panel + LED駆動回路

SSH = SSF + ADボード

SSD = SSH + 筐体

2024/6/5

							
型番	1916-B	1945-B	2125-A	2368-C	2405-M	2445-M	2805-A
サイズ (インチ)	19.1" (21.5 cut1/3)	19.4" (21.5 cut1/2)	21.2" (24" cut1/3)	23.6" (Circle)	24" (27" cut1/3)	24.4" (27" cut1/2)	28" (32" cut1/3)
提供可能 モデル	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SCD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD
有効表示 領域(mm)	476.064(H)x96.2(V)	476.06(H)x132.9(V)	531.36(H)x87.4(V)	596.16(H)x596.16(V)	597.8(H)x112.1(V)	698.4(H)x196.3(V)	698.40(H)x130.95(V)
輝度 (cd/m ²)	1200 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²
解像度	1920x388	1920x536	1920x316	1920x1920	1920x360	1920x540	1920x360
視野角	178° (H), 178° (V)	178° (H), 178° (V)	170° (H), 160° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)
消費電力 (W)	16.5W	23.9W	16W	61W	27W	31.7W	25.5W
外形寸法 (WxHxD mm)	508.01x132.00x47.05	499.6x152.3x31.8	558.5x119.5x46.1	890x890x77.2	626x201.5x44	617.9x198x42.9	737x170x57.9

「Spanpixel」シリーズ

SSF = LCD Panel + LED駆動回路

SSH = SSF + ADボード

SSD = SSH + 筐体

2024/6/5

型番	2861-Y	2869-Y	2940-Y	2945-A	2955-I	NEW 3325-Y	3525-I
サイズ (インチ)	28.6" (32" cut1/2)	28.6" (32" cut1/2)	29.4" (32" cut2/3)	29.4" (32" cut2/3)	29.5" (Square)	33.2" (Square)	35.2" (55" cut1/2)
提供可能 モデル	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD
有効表示 領域(mm)	698.4(H)x196.4(V)	698.4(H)x196.4(V)	698.4(H)x261.9(V)	698.4(H)x261.9(V)	529.4(H) x 529.4(V)	596.16(H)x596.16(V)	582.75(H)x680.4(V)
輝度 (cd/m ²)	3200 cd/m ²	1800 cd/m ²	2000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²
解像度	1920x540	1920x540	1920x720	1920x542	2160x2160	1920x1920	1850x2160
視野角	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)
消費電力 (W)	55W	39W	64W	40W	76W	60W	83W
外形寸法 (WxHxD mm)	734.5x232.5x60.1	734.5x232.5x60.1	738x305.2x58.9	738x305.2x61.9	564.5 x 564.5 x 61.4	615.8x615.8x62.9	629x710.4x73.5

3

※ 消費電力・外形寸法は、SSDの仕様値です。該当品がない場合は、それに準ずる製品の仕様値です。
 ※ 本仕様は予告なく変更されることがあります。
 ※ 最新データは、<http://plazmonic.jp/files/Spanpixel.pdf>をご参照ください。

「Spanpixel」シリーズ

SSF = LCD Panel + LED駆動回路

SSH = SSF + ADボード

SSD = SSH + 筐体

2024/6/5

型番	3565-I	3585-Y	3665-I	3685-I	3701-Y	3705-Y	3805-I
サイズ (インチ)	35.6" (55" cut1/2)	35.8" (40" cut1/2)	36.5" (42" cut1/4)	36.8" (42" cut1/3)	38" (42" cut1/2)	38" (42" cut1/2)	37.6" (42" cut1/2)
提供可能 モデル	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD
有効表示 領域(mm)	598.5(H)x680.4(V)	878.1(H)x239.1(V)	919.296(H)x138.8(V)	919.3(H)x171.4(V)	904.32(H)x254.34(V)	904.32(H)x254.34(V)	919.296(H)x258.5(V)
輝度 (cd/m ²)	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²	3000 cd/m ²	1000 cd/m ²	1000 cd/m ²
解像度	1900x2160	1920x532	1920x290	1920x358	1920x540	1920x540	1920x540
視野角	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)
消費電力 (W)	73W	60W	24W	27W	91.2W	77W	36.4W
外形寸法 (WxHxD mm)	629x710.4x73.5	898x268.1x77.2	962.8x177x56.2	962.8x210.1x56.2	938.5x290.5x61.8	938.5x290.5x61.8	962.6x304.9x54.2










「Spanpixel」シリーズ

SSF = LCD Panel + LED駆動回路

SSH = SSF + ADボード

SSD = SSH + 筐体

2024/6/5

	 	 	 	 	 		
型番	4221-Y	4225-Y	4305-Y	4851-Y	4855-Y	4959-I	5745-I
サイズ (インチ)	42.2" (47" cut1/2)	42.2" (47" cut1/2)	43" (49" cut1/3)	48" (55" cut 1/3)	48" (55" cut 1/3)	49.5" (55" cut 1/2)	57.4" (65" cut 1/3)
提供可能 モデル	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD	SSF/SSH/SSD
有効表示 領域(mm)	1039.68(H)x259.92(V)	1039.68(H)x259.92(V)	1073.7(H)x201.3(V)	1209.6(H)x266.8(V)	1209.6(H)x266.8(V)	1209.6(H)x340.2(V)	1428.4(H)x301.3(V)
輝度 (cd/m ²)	3000 cd/m ²	1000 cd/m ²	1000 cd/m ²	3000 cd/m ²	1000 cd/m ²	1800 cd/m ²	1000 cd/m ²
解像度	1920x480	1920x480	3840x720	1920x360	3840x720	3840x1080	3840x1080
視野角	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)	178° (H), 178° (V)
消費電力 (W)	132W	67W	57W	75W	57W	115W	89.8W
外形寸法 (WxHxD mm)	1072.8x296.9x66.1	1062.5x286.5x84.7	1114.9x 231.1x 70.8	1235x252.2x66	1235x 252.2x 70.3	1247.2x381.3x68.4	1465.4x336.8x65.1