



DLD1040-I

10.4" TFT LCD, 2000 nits LED Backlight, 1024x768

The **DLD1040-I** is a 10.4 inch industrial grade sunlight readable LCD, with high brightness **2000** nits, it produces sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.

Key Features

- 10.4" sunlight readable, high brightness
- Resolutions: 1024x768
- LED Backlight
- Aspect ratio of 4:3
- Wide temperature (-30°C~80°C)
- Low power consumption
- BL MTBF: 100,000 hours



Specifications

Model Name	DLDL1040-I
Description	10.4" TFT LCD, 2000nits LED Backlight, 1024x768
Screen Size	10.4"
Display Area (mm)	210.432 (H) x 157.824(V) mm
Brightness	2000 cd/m ²
Resolution	1024x768
Aspect Ratio	4:3
Contrast Ratio	1300 : 1
Pixel Pitch (mm)	0.2055(H) x 0.2055(V)
Pixel Pre Inch (PPI)	123
Viewing Angle (Min.)	178°(H),178°(V)
Color Saturation (NTSC)	76%
Display Colors	16.7M
Response Time (Typical)	25ms
Panel Interface	LVDS
Input Interface	HDMI, DP
Input Power	DC 12V
Power Consumption	12W
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, H/V Position...etc
Dimensions (mm)	233.6 x 181 x 46 (T)
Bezel Size(U/B/L/R)	11.59/11.59/11.59/11.59mm
Weight (Net)	1.25 kg
Mounting	VESA 75x75, 100x100 mm
Operating Temperature	-30°C ~ 80°C
Storage Temperature	-30°C ~ 80°C

DLD= Panel + LED Driving Board + AD Control Board + Chassis




*Specifications are subject to change without notice.
All brands or product names are trademarks or registered trademarks of their respective companies.*






Mechanical Drawing

Outline Dimensions

Unit:mm





NOTE :

O.D : OUTLINE DIMENSION

B.O : BEZEL OPENING

A.A : LCD ACTIVE AREA

A : 8-M4_USER_HOLE_MAX. DEPTH=4mm



Ordering Information

Part Number	Description
DLD1040-INB-T11	10.4",2000nits,1024x768,T3080,LID10C,AD68862HP,O/B,DC12V,5in1,V1

Optional Accessories

Part Number	Description
840612051212	ADAPTER,AC/DC,12V/5A,60W.Power-Din-4P,CWT.G99-ABF060F-N022.Efficiency-level-6,R
810618301010	CABLE,POWER,AC,1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE,POWER,AC,1830mm UK type
810618301170	CABLE,POWER,AC,1830mm Australia type
810618301030	CABLE,POWER,AC,1830mm Japan type

Customer request

Touch	PCAP Touch (Multi-Touch)
Glass	Tempered glass, AR coating.....